

MAXIMATOR®

Technical Sheet Release: 1/2003	S350-S	Oil and water service
	Technical Data:	
	Air Drive Pressure:	1–10 bar/14,5–145 psi
	Maximum permitted outlet Pressure:	3,000 bar/ 43,500 psi static; 1,800 bar / 26,100 psi dynamic
	Pressure ratio:	1 : 350
	Calculated displacement Volume/Double Stroke:	1.3 cm ³
	Connections:	
	Inlet:	¼ BSP Standard: Side inlet
	Outlet:	9/16-18UNF
	Air Drive:	½ BSP
	Maximum Operating Temperature:	60°C
	Net weight:	7 kg
	<i>Pressure and flow performances, please see enclosed graph.</i>	
	Materials of Construction:	Top cap:
	Air cylinder:	Aluminum hard coat
	Seal Package:	Polyurethane, Buna N
	Pump Body:	Stainless steel 1.4313
	HP Piston:	Stainless steel 1.4112
Approximate Dimensions:	Height:	289
	Depth:	140
	Width:	175
Available Options:	Bottom inlet	S350
	Special inlet and outlet ports, i.e. NPT	S350-NPT
	Special seal material to handle special fluids on request.	
Available Accessories:		
Air control units for S series with filter pressure regulator, control pressure gauge and shut-off valve:	S350-S with C1.5	
To protect the pump against excessive outlet pressures or to limit the outlet pressure, a safety valve can be fitted to the air control unit in the air drive line:	S350-S with C1.5/SVair (The required outlet pressure has to be indicated.)	

Please consult factory for more information.

All technical and dimensional information subject to change. All General Terms and Conditions of sale, including limitations of our liability, apply to all products and services sold.

MAXIMATOR GmbH

37449 Zorge/Germany, Walkenrieder Str. 15, Tel.: ++49 (0) 5586 803 0, Fax: ++49 (0) 5586 803 40

e-mail: info@maximator.de, website: www.maximator.de

Dimension Drawing S350-S

Standard pump comes with side inlet, bottom inlet available as option.



